

GENERAL

VARMEPUMPER

Veggmontert, inverter



R-410A - Store

TYPE INNEDEL	ASHG18LFC	ASHG24LFC	ASHG30LFC
TYPE UTEDEL	AOHG18LEC	AOHG24LFC	AOHG30LFC

Eurovent klasse		A	A	B
Kjølekapasitet	kW	5,2 (0,9 - 6)	7,1 (0,9 - 8)	8 (2,9 - 9)
Varmekapasitet	kW	6,3 (0,9 - 9,1)	8 (0,9 - 10,6)	8,8 (2,2 - 11)
COP faktor	ved +7°	3,68	3,61	3,61
COP faktor	ved -7°	2,27	2,22	2,27
Maks varme ved -5°/-15°	kW	6,48 / 4,84	7,84 / 5,9	9,15 / 7,38
Tilført effekt, varme	kW	1,71 (0,09 - 2,87)	2,21 (0,28 - 4,21)	2,44 (0,5 - 4,33)
Strømforbruk	A	6,8 / 7,6*	9,7 / 9,8*	10,9 / 10,7*
Luftmengde innedel	m3/h	620 - 900	620 - 1100	620 - 1100
Luftmengde utedel	m3/h	2070	2340	3600
Lydnivå innedel	db(A)	25/33/37/42	32/37/42/48	33/37/42/49
Lydnivå utedel	db(A)	50	52	53
Dimensjoner innedel (HxBxD)	mm	320 x 998 x 238		
Dimensjoner utedel (HxBxD)	mm	620 x 790(+60) x 298	578 x 790(+60) x 315	830 x 900 x 330
Vekt innedel	kg	14	14	14
Vekt utedel	kg	40	43	61
Rørdimensjoner "	væske	1/4"	1/4"	3/8"
	gass	1/2"	5/8"	5/8"
Maks rørlengde / høyde	m	25 / 20	30 / 20	50 / 30
Kuldemedie R-410a	g	1200	1600	2200
Anbefalt sikring	A	16c	20c	20c
Spenning	v / - / hz	230 / 1 / 50		



Mvh, Svein Erik Damli
 E-post : svein@damli.no
 Mobil : +47 922 98 390
<http://www.midtnorgevarme.no>

